



Metaltech srl | Via Saviabona 113/G | 36010 | Cavazzale di Monticello Conte Otto (VI) | ITALIA C.F. e P.IVA 03955300243 | Reg. Imprese VI: 03955300243 | REA: VI - 367516 | Cap. Soc. € 10.000,00 i.v.





# TECHNICAL DATA SHEET WHITECH3015C - 750 %

Master alloy for the production of white nickel free 750 % gold jewellery obtained by investment casting. This product, thanks to its complex composition made of numerous different special elements, ensures an extreme quality, an enhanced fluidity and a long lasting of this features also after many reuses of scraps, making it the most advanced nichel free master alloy for white gold.

### TAB.1 - Mechanical data

Hardness as cast	183 HV
Hardness hardened	n.d.
Tensile strength	n.d.
Yield strength	n.d.
Elongation	n.d.

# TAB.2 - Physical data

Color	Premium white			
Colour Coordinates	L*: a*: b*:	80.55 3.09 8.37		
Density		16.71	g/cm3	
Melting Range	Solidus: Liquidus:	806 904	°C °C	

# TAB.3 - Heat treatments

Solution annealing	630 30	°C min
Recrystallization Annealing	630 30	°C min
Hardening	n.d.	







Metaltech srl | Via Saviabona 113/G | 36010 | Cavazzale di Monticello Conte Otto (VI) | ITALIA C.F. e P.IVA 03955300243 | Reg. Imprese VI: 03955300243 | REA: VI - 367516 | Cap. Soc. € 10.000,00 i.v.

## TAB.4 - Investment casting parameters

Premelting temperature			see paragraph below
Casting Temperature	Min: Max:	954 1054	°C
Water investment powder ratio		36-38	%
Flask temperature	Min: Max:	450 600	°C °C
Quenching time without stones in place	Min: Max:	10 20	min min
Quenching time with stones in place		15	min in boiling water
Pickling			see paragraph below

# PREMELTING (MANDATORY)

A premelting of the master alloy and fine gold must be done to homogenize the alloy in the best way. For a proper premelting, first put the fine gold in the crucible and then switch on the power until 1100°C (make sure that the metal becomes liquid). After this, put the master alloy inside the liquid gold and, with a stirrer, push down the master alloy inside the gold, then decrease the temperature to 950-1000°C and pour into an ingot or do a granulation.

# **QUENCHING**

It's recommended to keep the flask inside the casting machine as long as possible before quenching, to limit the oxidation of the alloy by reducing its exposure in the air.

## **PICKLING**

For a proper pickling, use a concentrated solution of sulfuric acid at  $60 - 65^{\circ}$ C for 20 mins or a 50 % solution of hydrochloric acid at  $60 - 65^{\circ}$ C for 10 min.